

Product data sheet

TERRA SPIKE® XP



Deep aeration and removal of compaction to a depth of 16".

The TERRA SPIKE® XP was especially developed for Golf Greens, Fairways, Sportsgrounds and other turfs. High performance, excellent working quality, a very user friendly setup, a rugged heavy duty design and high durability have been the main tasks in development and were successfully realised.

TECHNICAL DATA	TERRA SPIKE® XP		
Model:	XP 6	XP 8	
Working width in inches:	63 "	83 "	
Weight in lbs. (approx.):	2116	2646	
Working depth in inches with solid tines/hollow tines up to:	16 " / 10 "		
Dimensions L / W / H in inches (approx.):	52 " / 85 " / 64 "	52 " / 104 " / 64 "	
Mounting:	rear three point cat. I and II		
QuickSet / QuickFit / PowerPack / VibraStop:	standard / standard / standard / standard		
Minimum required tractor power (recommended):	32 HP	42 HP	
Crankshaft speed:	145 RPM	165 RPM	187 RPM
Maximum admissible tractor power:	23 HP	30 HP	40 HP
Minimum tractor lifting capacity with standard attachment in lbs.:	3064	3726	
Tractor PTO speed:	540 RPM		
Solid tines Ø in inches:	3/16", 5/16", 1/2", 3/4", 1"		
Hollow tines Ø in inches:	1/2", 5/8", 3/4", 1"		
Rear roller:	standard		
Turf retainer:	optional		
Hydraulic depth adjustment:	optional		
Core collection scraper with rear roller:	optional	-	
Swath board:	optional		
Hydraulic rotary brush:	optional		
Additional weights:	optional		
Bogey:	optional		
Multi-tine holders for solid tines 3/16", 5/16" and 1/2":	optional		
Multi-tine holders for hollow tines of 1/2", 5/8" and 3/4":	optional		

Area coverage in continuous operation in square feet per hour at a crankshaft speed of:

187 RPM; at 0.47 mph; square hole spacing 2 1/2": (approx.):	20 holes/sq.ft. = 12,917 sq.ft./hr	20 holes/sq.ft. = 16,953 sq.ft./hr
187 RPM; at 0.95 mph; square hole spacing 5": (approx.):	5 holes/sq.ft. = 25,833 sq.ft./hr	5 holes/sq.ft. = 33,906 sq.ft./hr

Descriptions and illustrations are non-binding. We reserve the right to modify the construction and design.

